7F, No. 349, Sec. 2, Renhe Road, Dashi, Taoyuan, Taiwan 320

Revision: P0

AlinGaP LED DICE

Part NO.: AOC-8120xM-Au Series

PRELIMINARY

7-1S-2000-073


Features


- Orange color emission
- Excellent performance & high efficiency
- Great reliability even in harsh environment
- Mirror reflector to increase efficiency

Description

AOC-812OxM series is a orange color emitting AlInGaP LED grown by MOCVD technique. Its structure enables enhanced quantum efficiency; the mirror reflector greatly increases the light extraction efficiency and therefore a greater light intensity. This device is designed for ultra-high brightness (UHB) automobile, display, and consumer electronic applications.

Chip Dimensions





Emitting Area: 12mil×12mil ± 1mil Bonding Pad: $\phi 100 \mu m \pm 10 \mu m$

Cat No.:

Chip Thickness: 100μm ±10μm

Electrical and Optics Characteristics

Measuring Item	Symbol	Condition	Min	Тур.	Max	Unit
Forward Voltage	$V_{\rm F}$	$I_F=20mA$	1.90	-	2.40	V
Reverse Current	IR	V _R =5V	-	-	1.0	μA
Dominant Wavelength	λd	$I_F=20mA$	600	-	617	nm
Max. Junction Temperature	T_{max}	-	125			
Max. DC forward current	I_{f}	Ta = 25	70		mA	
Storogo topperature	т	Chip on tape	0 ~ 40			
Storage temperature	$T_{\rm stg}$	Only chip	-40 ~ 80			

Available Dominate Wavelength and Iv Matrix

Part No.	Wavelength Range	≥ 600 mcd	≥ 700 mcd	≥ 800 mcd
812 OxM	600 ~ 617 nm	Y60	Y70	Y80

Note:

- All measurements are done with AOC's standard testing equipment.
- Luminance intensity is measured on bare chip.

 Above contents are subject to change without notice.
- Special requests are also welcome, please contact AOC's sale representative for any request.

Characteristics curves are measured within TO-46 package, different result may caused by packaging method.

http://www.aocepi.com. Rev.00