

AlGaInP/GaAs Soft Orange Chip ---TK0509SON

1. Scope

- The specification applies to AlGaInP LED chips.
- Type : TK0509SON.

2. Structure

- AlGaInP/GaAs soft orange LED chip.
- Electrode P (anode) side : Aluminum or Gold.
- Electrode N (cathode) side : Gold alloy.

3. Size

- Chip size : $225\mu\text{m} \times 225\mu\text{m}$
- Chip height : $180\mu\text{m} \pm 30\mu\text{m}$
- Pattern drawing : per fig. 1


4. Electro-Optical Characteristics

($T_a = +25^\circ\text{C}$)

Parameter	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V_F	$I_F = 20\text{ mA}$		2.00	2.30	V
Reverse Voltage	V_R	$I_R = 10\text{ }\mu\text{A}$	5			V
Luminous Intensity	I_V	$I_F = 20\text{ mA}$		※		mcd
Wavelength	λ_p / λ_d	$I_F = 20\text{ mA}$		610/605		nm
Spectrum Width of Half Value	$\Delta \lambda$	$I_F = 20\text{ mA}$		20		nm

- ※
- Rank H : min. ≥ 50.0 , $65.0 \leq \text{avg.} < 75.0$
 - Rank I : min. ≥ 60.0 , $75.0 \leq \text{avg.} < 85.0$
 - Rank J : min. ≥ 65.0 , $85.0 \leq \text{avg.} < 95.0$
 - Rank K : min. ≥ 80.0 , $95.0 \leq \text{avg.} < 105.0$

- Rank L : min. ≥ 90.0 , $105.0 \leq \text{avg.} < 115.0$
- Rank M : min. ≥ 90.0 , $115.0 \leq \text{avg.} < 125.0$
- Rank N : min. ≥ 110.0 , $125.0 \leq \text{avg.} < 135.0$
- Rank O : min. ≥ 110.0 , $135.0 \leq \text{avg.} < 145.0$



Unit : μm




fig. 1

2012.May



☐ TYNTEK Head Office
☐ TYNTEK Chunan Branch
[http : //www.tyntek.com.tw](http://www.tyntek.com.tw)

Tel : 886-3-5781616
Tel : 886-37-582997


Fax : 886-3-5780545
Fax : 886-37-582908

E-mail : service@serv.tyntek.com.tw


AlGaInP/GaAs Soft Orange Chip ---TK0509SON

Electro-Optical Characteristics Curve


Forward current vs. Forward voltage




Relative intensity vs. Forward current




Forward voltage vs. Temperature



Relative intensity vs. Temperature



Relative intensity vs. Wavelength



☐ TYNTEK Head Office
☐ TYNTEK Chunan Branch
[http : //www.tyntek.com.tw](http://www.tyntek.com.tw)

Tel : 886-3-5781616

Tel : 886-37-582997

E-mail : service@serv.tyntek.com.tw

Fax : 886-3-5780545

Fax : 886-37-582908